

Product: [0935 613 302](#) 

CANopen / DeviceNet, Cordset, single ended: 7/8", Male, Straight, 5 pole, with cable type, Grey, PVC, DeviceNet THICK




Product Description


CANopen / DeviceNet, Cordset, single ended: 7/8", Male, Straight, 5 pole, with cable type, Grey, PVC, DeviceNet THICK

Technical Drawing

Faceview MINI 7/8" Male



- 1 = Cu
- 2 = RD
- 3 = BK
- 4 = WH
- 5 = BU



Technical Specifications

Technical Data

Product Family:	Data Connectors
Product Sub Family:	7/8"
Brand:	Lumberg Automation
Connector Type:	Cordset, single ended
Type of Contact / Gender:	Male
Connector Design:	Straight
Number of Pins:	5
Coding:	A
Shielding:	Shielded
Attachment Type:	Coupling Screw with external threads
Rated Voltage:	300 V
Rated Current*:	8 A

Data Transmission:	CANopen / DeviceNet
Mating Cycles:	max. 50
Cable Gland:	M16 x 1.5, color see standard article
Ambient Temperature (Operation)*:	- 40 °C - + 90 °C
Protection Degree / IP Rating**:	IP65, IP67
Pollution Degree:	3

Materials

Contact Base Material:	CuZn
Contact Plating:	gold over silver plated
Contact Bearer Material:	TPU
Contact Bearer Color:	Yellow
Molded Body Material:	TPU
Molded Body Color:	Grey
Housing Material:	TPU
Housing Color:	yellow
Attachment Material:	Al, anodized black
Gasket Material:	NBR

Cable Data

Cable Number:	613
Conductor Size:	max. 1.5 mm ²
Number of Wires:	2 Pair + Drain
Minimal Bending Radius (Fixed Inst):	> 7 x D
Minimal Bending Radius (Flexible Inst):	> 10 x D
Cycles (Bending):	> 1 M
Cable Jacket Material:	PVC
Cable Jacket Color:	Grey
Cable Diameter D:	Ø 12.1 mm
Wire Insulation Material:	PVC-Power, Data-PE
Insulated Wire Diameter:	Power Ø2.77 mm, Data Ø3.81 mm
Overall Shield (Cable):	Braid, TC, 65% Coverage
Ambient Temperature (Fixed Installation):	- 20 to + 60°C (60°C UL)
UL Cable Type:	CMG, PLTC-ER or UL AWM 20201, CSA AWM I/II A/B
Flammability Class (Cable Jacket):	FT4, IEC 60332-1-2
Cable Characteristics:	Mechanical Resistances, Abrasion, Impact, Weathering; Chemical Resistances to Oils, Acids, Alkalis

Safety & Environmental Compliance

RoHS Compliant:	Yes
-----------------	-----

Resistances

Oil Resistance:	Yes
-----------------	-----

Notes

Note Derating:	Notice derating
Protection Degree / IP Rating Note:	Protection Degree and IP Rating per test standard IEC 60529 using a Lumberg Automation mating product

Variants

Item #	Item Description	Cable Length
900005122	0935 613 302/0.6M	0.6 m
900001756	0935 613 302/1M	1 m
910001756	0935 613 302/1M-Y	1 m
900001746	0935 613 302/2M	2 m
910001746	0935 613 302/2M-Y	2 m
900001591	0935 613 302/3M	3 m
71277	0935 613 302/3 M	3 m
910001591	0935 613 302/3M-Y	3 m
900001961	0935 613 302/5M	5 m
910001961	0935 613 302/5M-Y	5 m

900002937	0935 613 302/6M	6 m
53655	0935 613 302/6 M	6 m
910002937	0935 613 302/6M-Y	6 m
900003070	0935 613 302/10M	10 m
910003070	0935 613 302/10M-Y	10 m

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.